

SUN SERIES

144 Half-Cut Cells - Bifacial

- IDEAL FOR LARGE SCALE UTILITY PROJECTS

Electrical Data (STC)

Maximum Power (Pmax) (+0 ~ 4.99 Wp)	530	535	540	545	550
Maximum Power Voltage, (Vmp)	40.56 V	40.63 V	40.70 V	40.80 V	40.90 V
Maximum Power Current (Imp)	13.07 A	13.17 A	13.21 A	13.36 A	13.45 A
Open-Circuit Voltage (Voc) ± 5%	49.26 V	49.34 V	49.42 V	49.52 V	49.62 V
Short-Circuit Current (Isc) ± 5%	13.71 A	13.79 A	13.85 A	13.94 A	14.03 A
Module Efficiency STC (%)	20.55%	20.75%	20.94%	21.13%	21.33%

*Values without tolerance are typical numbers.

Standard Test Condition (STC): Cell Temperature 25°C, Irradiance: 1000 W/m², AM : 1

Electrical Characteristics with different rear side power gain (Reference 550 Wp Front @ STC)

Bifaciality Gain	3%	5%	10%	15%	20%
Maximum Power (Pmax)	563	572	594	616	638
Maximum, Power Voltage, Vmpp (V)	41	41.01	41.02	41.03	41.04
Maximum Current, Impo(AI)	13.85	14.12	14.8	15.47	16.14
Open Circuit Voltage, Voc(M)	49.72	49.82	49.92	50.02	50.12
Short Circuit Current, Isc(A)	14.45	14.73	15.43	16.13	16.84

Bifaciality Factor: 80 ± 20% *Back-side power gain varies depending upon the specific project albedo

Mechanical Data

Panel Type	Bi-Facial / Mono-Facial Panels
Dimensions (mm) (± 2mm)	2278 mm (L) x 1134 mm (W) x 30/35 mm (T)
Dimensions (inch) (± 0.079)	89.68 in (L) x 44.64 in (W) x 1.18/1.38 in (T)
Weight (kg)	28 kg ~
Weight (lbs)	61.73 lbs ~
Solar Cell	144 (12 x 12) nos. Half cut M10 cells
Frame	Anodized Aluminium Black/Silver
Junction Box	UL Approved - IP68 with 3 diodes
Cable	1200mm / 300mm Length, 4 Sq. mm, 6.3mm diameter
Connector	MC4 Connector / Stabuli Connector (optional)

Operating Conditions

Mechanical Load (Wind/Snow)	2400 Pa Rear Load / 5400 Pa Front load
Hail Impact Resistance	25 mm dia. with 1 Inch at 51.6 mph
Maximum System Voltage	1500 V
Series Fuse Rating	25 A
Operating Temperature	-40 °C to +85 °C

Temperature Characteristics

Nominal Module Operating Temperature	45 °C ± 2 °C
Temperature Co-efficient of Isc	0.04 % / °C
Temperature Co-efficient of Voc	-0.259% / °C
Temperature Co-efficient of Pmax	-0.34% / °C

Shipping Specs (Vertical Packaging)

Modules / Pallet	31
Pallets / 40 ft HQ container	20

KOSOL ENERGIE INC.


USA Office: 445 Hotel Cir S, San Diego, CA 92108, USA

☎ +1 (619) 400-6667 ✉ globalsales@kosol.solar 🌐 www.kosol.solar

CAUTION: READ SAFETY AND INSTALLATION MANUAL BEFORE USING THE PRODUCT. Specifications included in this datasheet are subject to change without notice. Please confirm your exact requirements with the company representative before placing the order and finalizing the confirmation.

KOSOL ENERGIE

THE ENERGIE ENGINEERS



Certifications



UL - 61730 - 1 & 2 (CAN/CSA),
CEC

UL Fire Class - 1
Application Class - A
Electrical safety Class - II

IEC 61215 : 2021
IEC 61730-1 & 2 : 2023

IEC 62716 : 2013
IEC 61701 : 2020
IEC TS 62804 - 1 - 1 : 2020
IEC TS 63342 : 2022

IEC 61853 -1 (PAN File "[Download](#)")



Warranty

Product Warranty	10 years
Performance Warranty	25 years
Linear Power	≥ 98.00% end 1 st Year
Performance	≥ 92.33% end 10 th Year
Warranty	≥ 82.88% end 25 th Year

