

The Utility Player

19.2kW L2 CHARGER

Future-proof with all-purpose commercial flexibility
and 80A of pure charging precision

KEY FEATURES

- ➔ **~2.5 HOUR CHARGING TIME***
Perfect for commercial vehicle charging
- ➔ **SINGLE PORT DESIGN**
Increased reliability
- ➔ **FULL RANGE OF DEPLOYMENTS**
Suitable for commercial, workplace, fleet
depots, retail, healthcare, and hospitality



TECHNICAL SPECIFICATIONS

DESCRIPTION		80A
Input	Voltage	200-240 VAC, Single Phase
	Connection	L+G+N
	Frequency	50/60 Hz
	Current	80A
Output	Current	80A
	Power (continuous output)	80A
	Connector	SAE-J1772 Type 1
User Interface	Display	2.9 in OLED
	Push Buttons	RFID (standard)
	User Authentication	Emergency Stop
Mechanical	Dimensions (W x D x H)	785mm (30.9 in) x 275mm (10.8 in) x 1580mm (62.2 in)
	Weight	8 kg (17.6 lbs) - unit, cord, connector
	Charging Cable Length	5m (16 ft)
Network Connection		None
Environmental	Operating Temperature	-30°C (22°F) to +50°C (+122°F)
	Storage Temperature	-30°C (-22°F) to +70°C (+158°F)
	Humidity	<95% (non-condensing)
	Altitude	<2000m (6561ft)
	Ingress Protection	NEMA Type 3R
Protection	Cooling	Natural cooling
	Over voltage / Under voltage / Over current / Over temp / Surge / Residual current / Ground fault / Welding	

- Charger can be derated to as low as 16A.
- Wall mount only.



AUTOMOTIVE & FLEET



COMMERCIAL & HOSPITALITY



MARINAS, HARBORS & PORTS



SERVICE STATIONS & PARKING LOTS

FOR MORE INFORMATION OR TO PLACE AN ORDER:

+1-888-936-3744

info@eTreegoUS.com

eTreegoUS.com

*From 20% to 80% state of charge. Actual charging speeds may vary based on vehicle, environmental, and other factors and are not guaranteed.