



PHILADELPHIA SOLAR
DELIVERING CLEAN ENERGY SOLUTIONS

NEXUS

PS-MNB108(HCBF)-xxxW

Half-Cell N-Type 16BB Bifacial Module

445 - 460 Watt

Positive power tolerance of 0 ~+3%



Philadelphia Solar's Mono-Crystalline N-type modules with power up to **460Wp** are produced using the state-of-the-art (automated) robotic production lines. These modules are suitable to be used for most electrical power applications and have excellent durability to prevailing weather conditions

CERTIFICATIONS

UL 61215 / UL 61730
IEC 61215 / IEC 61730
CSA C22.2#61730:2019
HALT TEST Highly Accelerated Life And Extended Reliability Test
IEC 61853 PAN File
IEC TS 62804 PID Resistance
IEC 60068 Dust and Sand Resistance
IEC 62716 Ammonia Resistance
IEC 61701 Salt Mist Resistance
Bankability Report
EN ISO 9001: 2015
Quality Management System
EN ISO 14001: 2015
Environmental Management System
EN ISO 45001: 2018
Occupational health and safety management systems



Intertek



intertek



APPLICATIONS



On-Grid Commercial/
Industrial Roof-Tops



Off-Grid Systems
(Including Lighting Systems)



Solar Power Plants

FEATURES



Power output increases by 5-25% from the backside resulting in significantly reduced LCOE and (IRR).



Withstand High Mechanical load :
Front (5400 Pascal)
Back (5400 Pascal)



Exceptional Anti-PID performance through the use of optimized mass-production processes and strict materials control.



Improved light trapping and current collection technology enhance module power output and reliability.



Less partial shading current mismatch loss so more power output.




Better temperature coefficients come from half-cell design.



Made In Jordan

LINEAR PERFORMANCE WARRANTY



25 Year Product Warranty




30 Year Linear Power Warranty




Only -0.4% Annual Degradation

Electrical Performance & Temperature Dependence

Current-Voltage & Power-Voltage Curves (450W)




Temperature Dependence of I_{sc} , V_{oc} , P_{max}



ELECTRICAL CHARACTERISTICS				
POWER AT STC	445 W	450 W	455 W	460 W
Short Circuit Current - Isc (A)	14.38	14.47	14.54	14.62
Maximum Power Current - Impp (A)	13.40	13.44	13.48	13.52
Open Circuit Voltage - Voc (V)	38.76	38.84	39.02	39.15
Maximum Power Voltage - Vmpp (V)	33.23	33.51	33.76	34.03
Module Efficiency - η (%)	22.82%	23.08%	23.33%	23.60%
Bifaciality Ratio (%)	80% $\pm$ 5			
Power tolerance (%)	0~+3%			

Values at Standard Test Conditions STC (Air Mass AM 1.5, Irradiance 1000 W/m², Cell Temperature 25° C).

MATERIAL CHARACTERISTICS		MODULE DRAWINGS	
Characteristics	Value		
Cells per Module	108 (54x 2)		
Cell Type	N Type Mono-Crystalline		
Front Surface	3.2mm Tempered AR Coated Glass		
Back Cover	Transparent Backsheet		
Frame	Anodized Aluminum (Black/Silver)		
Junction Box	IP 68 With original MC4		
Cable Length	1200mm Cable length could be customized		
Fire Classification	Type 1		

THERMAL CHARACTERISTICS		PHYSICAL CHARACTERISTICS	
Characteristics	Value	Characteristics	Value
Open Voltage Temperature Coefficient VOC (%/C°)	-0.25	Module Dimensions (mm)	1721 x 1133 x 30
Short Circuit Current Temperature Coefficient ISC (%/C°)	+0.046	Module Weight (kg)	20.5±1Kg
Power Temperature Coefficient PMP (%/C°)	-0.29	Packaging	Value
NOCT (°C)	45±2	Modules per Pallet	37
OPERATING CONDITIONS		40 Feet High-Cube Container	962 Modules
Maximum System Voltage - Vmax (V)	1500	Mechanical Load**	Value
Maximum Series Fuse (A)	30	Max Static load (Front)	5400 Pa
Operating Temperature Range (°C)	IEC: -40 to +85 UL: -40 to +90	Max Static load (Back)	5400 Pa
		Dynamic load	1000 Pa

- ◆ Tolerance of power Current and Voltage (ISC,VOC)±3 %
- ◆ Datasheet is subjected to change without prior notice, always obtain the most recent version of the datasheet.
- ◆ ** Caution: For professional use only, the installation and handling of PV modules and cleaning modules require professional skills and should only be performed by qualified professionals, please read the Installation and Operation Manual before using the modules, also Cleaning Guidelines

