

Tier1

BloombergNEF



ISO 9001
ISO 45001

ISO 14001
OHSAS 18001



M10 TOPCON BIFACIAL


SPDGxxx-N144M10

555~595W


- Double glass
- Silver frame
- White mesh

25 Yr quality guarantee | 30 Yr power warranty

■ SUNPRO TOPCon module (Additional value from 30-year warranty)
■ Common module



*SUNPRO Standard tiered warranty



WARRANTY & GUARANTEE

Linear output power guarantee
25 years: 89.4% power output
30 years: 87.4% power output



WITHSTAND STRONG

Snow load 5400Pa
Wind load 2400Pa



PID RESISTANCE

Power positive tolerance :
0~+5W.
The attenuation probability of
PID phenomenon is
minimized through battery
production technology
optimization and material control



R&D AND PRODUCTION

Advanced production line.
Bifaciality>80%,effectively
improves backside power
generation.The leading
solar cell cutting process
and multi busbar design
with SUNPRO Technology.



HIGH EFFICIENCY

N-type , Components have
better reliability and
lower LID/LETID attenuation.
Efficiency can reach
23.02%. Excellent low light
performance. Higher power
output under the conditions
of haze, overcast, etc.

Electrical parameters at standard test conditions (STC:AM=1.5, 1000W/m², Cells Temperature 25°C)

Typical type

	555W	560W	565W	570W	575W	580W	585W	590W	595W
Max power(Pmax)	555	560	565	570	575	580	585	590	595
Max power voltage(Vmp)	41.86	41.99	42.13	42.26	42.41	42.56	42.72	42.87	43.03
Max power current(Imp)	13.26	13.34	13.41	13.49	13.56	13.63	13.7	13.77	13.83
Open circuit voltage(Voc)	50.7	50.84	50.98	51.13	51.28	51.43	51.58	51.7	51.84
Short circuit current(Isc)	14.01	14.07	14.13	14.2	14.27	14.34	14.41	14.48	14.55
Module Efficiency(%)	21.48	21.67	21.86	22.06	22.25	22.44	22.64	22.83	23.02
Max system voltage	DC 1500V (TÜV,UL)								
Maximum Series Fuse Rating	30A								

Electrical Characteristics with 15% Rear Side Power Gain


Front power Pmax/W	555W	560W	565W	570W	575W	580W	585W	590W	595W
Total power Pmax/W	638.25	644	649.75	655.5	661.25	667	672.75	678.5	684.25
Vmp/V(Total)	41.86	41.99	42.13	42.26	42.41	42.56	42.72	42.87	43.03
Imp/A(Total)	15.25	15.34	15.42	15.51	15.59	15.67	15.75	15.83	15.90
Voc/V(Total)	50.7	50.84	50.98	51.13	51.28	51.43	51.58	51.7	51.84
Isc/A(Total)	16.11	16.18	16.25	16.33	16.41	16.49	16.57	16.65	16.73

Electrical parameters at NMOT test conditions

(Irradiance 800W/m², Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s)

Typical type	555W	560W	565W	570W	575W	580W	585W	590W	595W
Max power(Pmax)	417	421	425	429	433	436.7	437.3	441	444.60
Max power voltage(Vmp)	39.3	39.5	39.7	39.7	39.9	40.1	39.9	40.0	40.20
Max power current(Imp)	10.62	10.67	10.72	10.79	10.85	10.90	10.96	11.02	11.07
Open circuit voltage(Voc)	47.7	47.9	48.1	48.2	48.4	48.5	48.3	48.4	48.50
Short circuit current(Isc)	11.29	11.34	11.39	11.44	11.50	11.56	11.61	11.67	11.72

DIMENSIONS AND STRUCTURE



Mechanical Data

Dimensions	2278x1134x30mm
Weight	31kg
Glass	(F) 2.0mm ultra clear embossed double layer colorless glass (B) 2.0mm white mesh glazed tempered glass
Output cables	4mm ² , symmetrical lengths 1300mm
Connectors	MC4 compatible IP68
Cell type	Mono-Crystalline, N type Bifacial, 182x91mm
Number of cells	144cells (Half-Cell)


Temperature Characteristics

Temp.Coeff.of Isc(TK Isc)	0.046%/°C
Temp.Coeff.of Voc(TK Voc)	-0.25%/°C
Temp.Coeff.of Pmax(TK Pmax)	-0.30%/°C
Operating temperature	-40~+85°C
Normal operating cell temperature	45±2°C

Packing Configuration

Container	40'HQ
Pieces per pallet	36
Pallets per container	20
Pieces per container	720

I-V CHARACTERISTICS AT DIFFERENT IRRADIATION



Tests, Certifications and Warranties

Standard tests	IEC 61215, IEC 61730, IEC 61701, IEC 62716, PPP 58042
System certs	ISO 9001, ISO14001, ISO45001
Certifications	TÜV, CE, CEC, UL, WEEE
Extreme wind and snow loads testing	Withstand extreme wind(2400 Pascal) and snow loads(5400 Pascal)
Power tolerance	0~+5W
Junction box	IP 68
Warranties	25 years product warranty and 30 years 87.4% of power

CORPORATE NAME: SUNPRO POWER NORTH AMERICA INC.

ADD: STE 2, 206 N Randolph St, Champaign, IL 61820 E-MAIL: info@sunpropower.com WEBSITE: www.sunpropower.us

*All data may have a lag, for reference only. Sunpro has the final right of interpretation.