

12
YEAR
QUALITY ASSURANCE

30
YEAR
POWER OUTPUT GUARANTEE

VSUN590N-144BMH

VSUN590N-144BMH

VSUN585N-144BMH

VSUN580N-144BMH

VSUN575N-144BMH

VSUN570N-144BMH

VSUN565N-144BMH

590W

Highest power output

22.84%

Module efficiency

1.0%

First-year
degradation warranty

0.4%

Annual degradation
over 30 years

KEY FEATURES

TOPcon TOPcon technology



Higher output power



MBB technology with
Circular Ribbon



Positive tolerance offer



Bifacial cells, converting more
sunlight into electricity



Better shading tolerance



Better temperature coefficient



Excellent PID Resistance



Lower LCOE



UL 61730 & CSA 61730
IEC 61215 & IEC 61730


ABOUT VSUN

Invested by Fuji Solar, VSUN SOLAR is a solar solution provider with headquartered in Tokyo, Japan that offers reliability, high efficiency solar products and technology globally. VSUN is rated as BNEF Tier 1 PV module manufacturer, PVEL Lab "Best performer" and EcoVadis "Bronze Award".

PRODUCT CERTIFICATION



WARRANTY



Electrical Characteristics at Standard Test Conditions(STC)

Module Type	VSUN590N-144BMH	VSUN585N-144BMH	VSUN580N-144BMH	VSUN575N-144BMH	VSUN570N-144BMH	VSUN565N-144BMH
Maximum Power - Pmax (W)	590	585	580	575	570	565
Open Circuit Voltage - Voc (V)	51.79	51.65	51.44	51.26	51.07	50.87
Short Circuit Current - Isc (A)	14.49	14.44	14.37	14.31	14.25	14.19
Maximum Power Voltage - Vmpp (V)	43.11	42.92	42.7	42.53	42.34	42.14
Maximum Power Current - Imp (A)	13.69	13.65	13.6	13.54	13.48	13.41
Module Efficiency	22.84%	22.65%	22.45%	22.26%	22.07%	21.87%

Standard Test Conditions (STC): irradiance 1,000 W/m²; AM 1.5; module temperature 25°C. Pmax Sorting : 0~5W. Measuring Tolerance: ±3%.

Remark: Electrical data do not refer to a single module and they are not part of the offer. They only serve for comparison among different module types.

Electrical Characteristics with different rear side power gain(reference to 585 front)

Pmax (W)	Voc (V)	Isc (A)	Vmpp (V)	Imp (A)	Pmax gain
614	51.65	15.16	42.92	14.33	5%
644	51.65	15.88	42.92	15.02	10%
702	51.73	17.33	42.84	16.38	20%
731	51.73	18.05	42.84	17.06	25%

Material Characteristics

Dimensions	2278×1134×35mm (L×W×H) 89.69×44.65×1.38 inches (L×W×H)
Weight	28.8kg / 63.49lbs
Frame	Silver anodized aluminum profile
Front Glass	AR-Coating toughened glass, 3.2 mm
Back sheet	Transparent white-mesh backsheet
Cells	12×12 pcs mono solar cells series strings
Junction Box	IP68, 3 diodes
Cable	Potrait: 500 mm (cable length can be customized) , 1×4 mm ² or 12AWG

System Design

Maximum System Voltage [V]	1500
Series Fuse Rating [A]	30
Bifaciality	80%±10%
Fire Rating	Class C for IEC and TYPE 1 for US
Protection Class	Class II
Temperature Range	-40 °C to + 85 °C
Maximum Surface Load	+5400/-2400 Pa +113/-50 psf
Application class	class A
Withstanding Hail	Maximum diameter of 25 mm with impact speed of 23 m/s

Packaging

Dimensions(L×W×H)	2310×1125×1253mm / 90.94×44.29×49.33inches
Quantity per pallet	31 pcs
Container 20'	155
Container 40'	310
Container 40'HC	620

Temperature Characteristics

NOCT	45°C(±2°C)
Voltage Temperature Coefficient	-0.26%/°C
Current Temperature Coefficient	+0.046%/°C
Power Temperature Coefficient	-0.30%/°C

Dimensions

IV-Curves

Note:mm (inch)

