BATTERY TO CHARGE CONTROLLER TRAY CABLES FOR 3/8 IN LUGS

RENOGY 4AWG WIRE COPPER SOLAR TRAY CABLES FOR CONNECTING CHARGE CONTROLLER TO BATTERY (A PAIR)

Length	8FT/16FT (20.3cm / 40.6cm)
Gauge (Wire Size)	4AWG / 21.2mm²
Terminal Size	3/8 in Lugs (M10)
Max. Current	95A
Rating Voltage	600/1000V
Temperature	-40°F to +185°F

RENOGY 8AWG WIRE COPPER SOLAR TRAY CABLES FOR CONNECTING CHARGE CONTROLLER TO BATTERY (A PAIR)

Length	8FT/16FT (20.3cm / 40.6cm)
Gauge (Wire Size)	8AWG / 8.4mm²
Terminal Size	3/8 in Lugs (M10)
Max. Current	55A
Rating Voltage	600/1000V

Temperature	-40°F to +185°F

RENOGY 10AWG WIRE COPPER SOLAR TRAY CABLES FOR CONNECTING CHARGE CONTROLLER TO BATTERY (A PAIR)

Length	8FT/16FT (20.3cm / 40.6cm)
Gauge (Wire Size)	10AWG / 5.3mm²
Terminal Size	3/8 in Lugs (M10)
Max. Current	30A
Rating Voltage	600/1000V
Temperature	-40°F to +185°F

RENOGY 12AWG WIRE COPPER SOLAR TRAY CABLES FOR CONNECTING CHARGE CONTROLLER TO BATTERY (A PAIR)

Length	8FT/16FT (20.3cm / 40.6cm)
Gauge (Wire Size)	12AWG / 3.3mm²
Terminal Size	3/8 in Lugs (M10)
Max. Current	20A
Rating Voltage	600/1000V
Temperature	-40°F to +185°F

WARRANTY INFORMATION	
Accessories	1-year material warranty