10A SOLAR CONNECTOR WATERPROOF IN-LINE FUSE HOLDER W/ FUSE	
Rated Current: 10A	Degree of Protection: IP2*/IP67
Rated Voltage: 1000 V DC	Flame Class: UL94-V0
Test Voltage: 6000V (50Hz,1 min)	Safety Class: II
Overvoltage Category: CATIII	Suitable Connector: Solar Connector
Contact Resistance of Plug Connector:1mΩ	Insertion Force / Withdrawal Force: ≤50N / ≥50N
Contact Material: Copper, Silver Plated	Fuse Can Replace
Insulation Material: PPO	Temperature Range: -40 to +125°C

15A SOLAR CONNECTOR WATERPROOF IN-LINE FUSE HOLDER W/ FUSE	
Rated Current: 15A	Degree of Protection: IP2*/IP67
Rated Voltage: 1000 V DC	Flame Class: UL94-V0
Test Voltage: 6000V (50Hz,1 min)	Safety Class: II
Overvoltage Category: CATIII	Suitable Connector: Solar Connector

Contact Resistance of Plug Connector:1mΩ	Insertion Force / Withdrawal Force: ≤50N / ≥50N
Contact Material: Copper, Silver Plated	Fuse Can Replace
Insulation Material: PPO	Temperature Range: -40 to +125°C

20A SOLAR CONNECTOR WATERPROOF IN-LINE FUSE HOLDER W/ FUSE	
Rated Current: 20A	Degree of Protection: IP2*/IP67
Rated Voltage: 1000 V DC	Flame Class: UL94-V0
Test Voltage: 6000V (50Hz,1 min)	Safety Class: II
Overvoltage Category: CATIII	Suitable Connector: Solar Connector
Contact Resistance of Plug Connector:1mΩ	Insertion Force / Withdrawal Force: ≤50N / ≥50N
Contact Material: Copper, Silver Plated	Fuse Can Replace
Insulation Material: PPO	Temperature Range: -40 to +125°C

30A SOLAR CONNECTOR WATERPROOF IN-LINE FUSE HOLDER W/ FUSE	
Rated Current: 30A	Degree of Protection: IP2*/IP67
Rated Voltage: 1000 V DC	Flame Class: UL94-V0
Test Voltage: 6000V (50Hz,1 min)	Safety Class: II
Overvoltage Category: CATIII	Suitable Connector: Solar Connector
Contact Resistance of Plug Connector:1mΩ	Insertion Force / Withdrawal Force: ≤50N / ≥50N
Contact Material: Copper, Silver Plated	Fuse Can Replace
Insulation Material: PPO	Temperature Range: -40 to +125°C

WARRANTY INFORMATION

Accessories	1-year material warranty