| RENOGY 10FT 10AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR) | |
|---|---|
| Length: 10ft | AWG: 10 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 6.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.85 | Min. Wall Thickness of Sheath (mm): 1.08 |
| Number of Wires in Conductor: 84 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| RENOGY 10FT 12AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR) | |
|---|---|
| Length: 10ft | AWG: 12 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 4.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.78 | Min. Wall Thickness of Sheath (mm): 0.97 |
| Number of Wires in Conductor: 56 | IP 65 Protection |

| | |
|---|---|
| Conductor: Tinned copper wire | |

| RENOGY 20FT 10AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR) | |
|---|---|
| Length: 20ft | AWG: 10 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 6.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.85 | Min. Wall Thickness of Sheath (mm): 1.08 |
| Number of Wires in Conductor: 84 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| RENOGY 20FT 12AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR) | |
|---|---|
| Length: 20ft | AWG: 12 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 4.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.78 | Min. Wall Thickness of Sheath (mm): 0.97 |

| | |
|---|---|
| Number of Wires in Conductor: 56 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| RENOGY 30FT 10AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR) | |
|---|---|
| Length: 30ft | AWG: 10 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 6.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.85 | Min. Wall Thickness of Sheath (mm): 1.08 |
| Number of Wires in Conductor: 84 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| RENOGY 30FT 12AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR) | |
|---|---|
| Length: 30ft | AWG: 12 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 4.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |

| | |
|---|---|
| Min. Wall Thickness of Insulation (mm): 0.78 | Min. Wall Thickness of Sheath (mm): 0.97 |
| Number of Wires in Conductor: 56 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| **RENOGY 40FT 10AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS(A PAIR)** | |
|---|---|
| Length: 40ft | AWG: 10 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 6.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.85 | Min. Wall Thickness of Sheath (mm): 1.08 |
| Number of Wires in Conductor: 84 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| **RENOGY 40FT 12AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR)** | |
|---|---|
| Length: 40ft | AWG: 12 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |

| | |
|---|---|
| Normal Cross Sectional Area of the Conductor (mm2): 4.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.78 | Min. Wall Thickness of Sheath (mm): 0.97 |
| Number of Wires in Conductor: 56 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| **RENOGY 9IN 10AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR)** | |
|---|---|
| Length: 9in | AWG: 10 |
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 6.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.85 | Min. Wall Thickness of Sheath (mm): 1.08 |
| Number of Wires in Conductor: 84 | IP 65 Protection |
| Conductor: Tinned copper wire | |

| **RENOGY 9IN 12AWG ADAPTOR KIT - CONNECTING SOLAR PANELS TO CHARGE CONTROLLERS (A PAIR)** | |
|---|---|
| Length: 9in | AWG: 12 |

| | |
|---|---|
| Rating Voltage: 600/1000V | Temperature: -40°F to +185°F |
| Normal Cross Sectional Area of the Conductor (mm2): 4.0 | Diameter of Wires in Conductor (mm): 3.02±0.08 |
| Min. Wall Thickness of Insulation (mm): 0.78 | Min. Wall Thickness of Sheath (mm): 0.97 |
| Number of Wires in Conductor: 56 | IP 65 Protection |
| Conductor: Tinned copper wire | |